

Wired Controller Compatibility Chart



Wired Controller Series	Part Code	Description	Sapphire	All Vireo & Vireo ULTRA	All Live
XE71 ^{1&2}	MC20700970	Single/Multi zone programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓
XE72 ²	MC20701210	Single/Multi zone programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓



XE71



XE72 WIFI



XK19



XK76 & XK60

Wired Controller Series	Part Code	Description	Multi Cassette	Multi Slim Duct	Multi Floor/Ceiling	Multi Mini- Console	U-Match Cassette /Floor- Ceiling /Slim Duct	U-Match Mini- Console
XK19	MC20700140	Used with all Multi Zones - programmable controller with touch buttons. Includes 26 ft. wire harness Part # 40010232 with Molex plugs.	✓	✓	✓			
XE71 ^{1&2}	MC20700970	May be used with all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓			
XE72 ²	MC20701210	<u>WIFI</u> for all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓			
XK76 ²	MC20700360	Single/Multi zone high wall programmable controller with touch pad. Includes (1) 26 ft. & (1) 6.5 in. wire harness with Molex plugs Part # 4003800101 & 4001024512	✓	✓	✓			
XK60 ³	MC20700550	U-Match & U-Match+ programmable controller with buttons & back light. Requires field supplied 18/2 AWG 300V [min] stranded wire. Max effective wire length is 26 ft.					✓	



Controller Included with Unit

Note: All Wired Controller wire harness is 26 ft., 26 ft. is the maximum length for effective operation. It should not be cut or spliced.

¹ XE71 May be used in lieu of the XK19, but, if used to replace an XK19 already installed the wire harness must also be replaced.

² These controllers can be used to set external static pressure on DUCT B models

³ XK60 Used with UMAT BD hi-static duct models to set external static pressure.

* REPRESENTATIVE IMAGES, ACTUAL PRODUCT MAY VARY, CHECK SALES LITERATURE.

Go to GreeComfort.com <https://www.greecomfort.com/resources/dealer-resources-current-product/>, see **Wired Programmable Controllers** Section for more information.